

Specifications

Amplifier Section

Power Output:	15 watts min. RMS per channel, both channels driven into 8 ohms from 20Hz to 20kHz, with less than 0.5% THD.
Power Bandwidth:	From 10Hz to 60Hz at less than 1% THD into 8 ohms, both channels driven simultaneously at 7.5 watts per channel.
Frequency Response:	From 5Hz to 80kHz, -3dB at less than 0.5% THD.
Square Wave Rise Time:	Better than 5 microseconds.
Square Wave Tilt:	Less than 5% at 20Hz full output.
Total Harmonic Distortion:	Less than 0.5% from 250 milliwatts, to 15 watts RMS, both channels driven simultaneously into 8 ohms from 20Hz to 20kHz.
Intermodulation Distortion:	Less than 0.2% at rated power output.
System Hum and Noise:	Better than 60dB below rated output (unweighted).
Damping Factor:	30.
Input Sensitivity:	Phono: 3mV. Aux: 200mV.
Input Impedance:	Phono: 47,000 ohms. Aux: 20,000 ohms.
Overload:	Phono: 70mV at 1kHz. Aux: Related to volume control setting.
RIAA Equalization:	± 1dB.

Tuner Section

FM Sensitivity:	3.5 microvolts, 1 HF.
Capture Ratio:	3dB.
Image Rejection:	40dB.
Alternate Channel Selectivity:	40dB.
Multiplex Separation:	25dB at 1kHz.
Dimensions:	16"W x 14"D x 4-1/4"H. (406mm x 356mm x 108mm).
Weight:	14 lbs (6.4kg).